



4 WALL SECTION AT CANTILEVER OVERHANG

3 WALL SECTION AT EXTERIOR ENTRANCE

2 WALL SECTION AT INTERIOR ENTRANCE

1 WALL SECTION AT REAR WINDOW

PARAPET (TYPICAL)
METAL FLASHING
50 WOOD BLOCKING

STEEL ANGLES:
100 X 100 STL. COL.
ON ST. PLATE
[SEE STRUCTURAL]
50 X 50 GALV. WELDMESH
CERAMIC TILE

1200 X 1200 DOMED PLASTIC SKYLIGHT

INSULATION

SCORED CONCRETE BLOCK

ROOF TERRACE (TYPICAL)
EPDM ROOFING MEMBRANE
75 INSULATION
50 CONCRETE PAVING SLABS

STL. BEAMS
SEE STRUCTURAL DRAWINGS

STEEL BEAM BEYOND

LAY IN GRID CEILING

VALANCE BEYOND

ALUMINUM WINDOW

GYPSUM BOARD ON STUDS AND/OR FURRING AS REQUIRED

OVERHANG (TYPICAL)
AIR/VAPOUR BARRIER ON 13 PLYWOOD BACKING
50 MINERAL FIBRE INSULATION/ 75 "Z" GIRTS
25 AIR SPACE
13 CEMENTITIOUS BOARD
16 STUCCO

INTERLOCKING PAVERS
150 X 150 STONE
EDGE CURB
150 LIMESTONE SCREEN
200 GRAVEL BASE

ASPHALT PAVING

50 INSULATION
MEMBRANE
WATERPROOFING

STAIR # 1
B001

BASEMENT FLOOR
125 CONCRETE SLAB

STL. BEAMS
SEE STRUCTURAL DRWG.

16 mm Gyp. board ceiling

CORRIDOR
108

STRUCTURAL STEEL BEAM

SERVERY
B002

STEEL ANGLES:
100 X 100 STL. COL.
ON ST. PLATE
[SEE STRUCTURAL]
50 X 50 GALV. WELDMESH
CERAMIC TILE

PRESCHOOL
208

EXTERIOR WALL (TYPICAL)
90 FACE BRICK
25 MINIMUM AIRSPACE
50 INSULATION
AIR BARRIER/ VAPOUR RETARDER
13 EXT. GRADE GYP. BOARD
100 LIGHTWEIGHT STEEL FRAMING
58" GYPSUM BOARD

STAIR # 2
109

STORAGE
B005

ALUMINUM WINDOW

1 WALL SECTION AT REAR WINDOW